

D611E CCD Dome IP Camera



Features:

- 1/3" SONY Super HAD High Resolution CCD Sensor
- 3.7 – 12mm Vari-focal lens
- Supports AGC, AES, AWB, Anti Color-Rolling
- Simultaneous MPEG-4 & MJPEG Dual Streaming
- Excellent Image Quality with up to 30 fps in Full D1 resolution
- Synchronized Two-way Audio
- Supports 3GPP/ISMA RTSP for Mobile Surveillance
- Intelligent Motion Detection
- Digital I/O port for external Alarm & Sensor
- PoE (Power over Ethernet) Built-in with IEEE 802.3af Class 0 support
- UPnP (Universal Plug'n'Play) for fast and easy installation
- User-friendly & Multi-lingual UI
- Bundled 16 Channel Surveillance Software

D611E CCD Dome IP Camera	
Models	D611E (NTSC), D611E (PAL)
Camera	1/3" SONY Super HAD high resolution CCD sensor, 520TVL 0.1Lux @ F1.4; AGC, AES, AWB, Anti Color-Rolling Electronic shutter: 1/60 - 1/1000000sec (NTSC), 1/50 - 1/1000000sec (PAL)
Lens	3.7 – 12mm, F1.4 Vari-focal lens
System	ARM9 based 32-bit RISC CPU, 8MB Flash, 64 MB RAM Embedded OS: Linux 2.4
Video Compression	MPEG-4, Motion JPEG Adjustable Bitrate (64Kbps to 2048Kbps), Quality and Bitrate
Video Resolution	Up to 30 frames at 704x480 (NTSC); Up to 25 frames at 704x576 (PAL)
Video Streaming	Simultaneous MPEG-4 & MJPEG (Dual Streaming) Supports Unicast & Multicast Supports 3GPP/ISMA RTSP (Real Time Streaming Protocol)
Audio	Two-way audio (full duplex)
Alarm and Event	Built-in multi-window motion detection Input x 1, Output x 1 for External Alarm & Sensor (DIDO) Triggered and scheduled events, Pre- and Post-alarm buffer
Supported Protocols	TCP/IP, DHCP, PPPoE, ARP, ICMP, FTP, SMTP, DNS, NTP, UPnP, RTSP, RTP, HTTP, TCP, UDP, 3GPP/ISMA RTSP
Security	ID/Password Authentication; SSL Protocol V3.0
Power	12V DC, 1A, Max 6W
PoE	PoE (Power over Ethernet) Built-in Supports Alternative A/B, Class 0, Max 12.95W
Connectors	Ethernet – RJ45 for 10/100 Base-T (with PoE) 12V DC Input x 1, Output x 1 for External Alarm & Sensor (DIDO) Analog video output (BNC) 3.5mm Audio Input, 3.5mm Audio Output
Operating Environment	0° - 50 °C (32° - 122°F) Humidity 20 - 80% RH (non-condensing)
Video Surveillance Software	Professional surveillance application for viewing, recording and archiving up to 16 cameras
Approvals	CE, FCC, RoHS
Dimension	110mm x 130mm (φ)